



INVESTOR IN PEOPLE

The Patent Office  
 Concept House  
 Cardiff Road  
 Newport  
 South Wales  
 NP10 8QQ

**PRIORITY  
 DOCUMENT**  
 SUBMITTED OR TRANSMITTED IN  
 COMPLIANCE WITH RULE 17.1(a) OR (b)

REC'D 08 APR 2004

WIPO

PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

*Andrew Gurney*

Dated... 25 March 2004

**BEST AVAILABLE COPY**

THE PATENT OFFICE  
E

Patents Form 1/77

Patents Act 1977  
(Rule 16)

14 MAR 2003

NEWPORT



17MAR03 E792649-1 002847

P01/7700-0 00-0305976.3

1/777

The Patent Office

Cardiff Road  
Newport  
South Wales  
NP10 8QQ

## Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

1. Your reference

HL81733/000/DLB

2. Patent application number

(The Patent Office will fill in this part)

14 MAR 2003

0305976.3

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Andrew Michael Wild  
Box BCM 3715, London WC1N 3XX  
United Kingdom

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

858 8 212001

4. Title of the invention

SURGICAL CLIP

5. Name of your agent (if you have one)

Haseltine Lake

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Imperial House  
15-19 Kingsway  
London  
WC2B 6UD

Patents ADP number (if you know it)

34001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number  
(if you know it)

Date of filing  
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing  
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if

No

- a) any applicant named in part 3 is not an inventor, or
  - b) there is an inventor who is not named as an applicant, or
  - c) any named applicant is a corporate body.
- See note (d))

# Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form 0  
Description 12  
Claim(s) 3  
Abstract 1  
Drawing(s) 5

*[Handwritten signature]*

10. If you are also filing any of the following, state how many against each item.

Priority documents 0  
Translations of priority documents 0  
Statement of inventorship and right to grant of a patent (Patents Form 7/77) 0  
Request for preliminary examination and search (Patents Form 9/77) 0  
Request for substantive examination (Patents Form 10/77) 0  
Any other documents (please specify) 0

11. I/We request the grant of a patent on the basis of this application.

Signature Haseltine Lake Date 14.3.03

12. Name and daytime telephone number of person to contact in the United Kingdom Mr David L Brown [0117] 910 3200

## Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

## Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

## **SURGICAL CLIP**

### **Field of the Invention**

5

The present invention relates to a surgical clip, particularly but not exclusively for use in haemostasis.

### **Background of the Invention**

10

An example of a commercially available haemostatic locking clip is the Hem-o-lok ligating clip, available from Weck Closure Systems, USA (web-site: [www.weckclosure.com](http://www.weckclosure.com)). This clip takes the form of a hinged plastic jaw with cooperating snap-fit closure formations on the end of each of the two jaw members. The clip is applied onto a blood vessel via a simple pliers-like applicator which closes the open jaw members together across the blood vessel, until the jaw members snap together. The clip has no inherent self closing bias, and the application mechanism is crude in that each clip must be loaded manually and individually on the applicator, in the open condition. To actuate the loaded applicator, a surgeon must make available his whole dominant hand, because of the pliers-grip hand action required.

20

A permanent occlusion cerebral aneurysm clip is on the market from Aesculap, under the name of the Yasargil-Phynox aneurysm clip. This clip takes the form of a spring-hinged cobalt-chrome (or sometimes titanium) metal alloy jaw provided with a self closing spring bias. The clip is applied onto a cerebral blood vessel via a simple pliers-like applier which initially opens the jaw members against the spring bias, so that the open jaw can be applied across the blood vessel. The applier can then be released, so that the jaw members spring together. Again, this clip suffers from the disadvantages that each clip must be loaded manually and individually on the applier, in the open condition, and, to actuate the loaded applier, a surgeon must make available his whole dominant hand, because of the pliers-grip hand action required.

30

WO-A-00/35355, the disclosure of which is incorporated herein by reference, describes a surgical apparatus and method for occluding or encircling a body passageway, e.g. for haemostasis. The method involves offering a surgical clip formed from a temperature-dependent shape-memory material, to a blood vessel or other body passageway in a first clip configuration at a temperature below body temperature, and allowing the temperature of the clip to rise by the proximity of the body passageway to the clip. The rise in temperature assists the clip to deform into a second, occluding, configuration in which the clip is closed around the body passageway.

One particular clip design is shown in Figures 19 to 21 of this prior art. The clip comprises an elongate element formed of circular cross-section shape-memory metal (Nitinol) wire shaped to have generally first and second ends and a sinuously curved intermediate central portion. The first and second ends of the wire element form legs of the clip and the sinuously curved intermediate central portion forms two apices directed towards the legs, which provide shoulders to which the closing force of the legs in the second configuration is directed. In effect, the legs of the clip squeeze the body passageway against the apices of the central portion of the clip to provide occlusion of the body passageway.

It is found that there is still room for improvement of the occlusive effect of the prior art clips.

### **Brief Description of the Invention**

The present invention is based on my finding that the occlusive effect of the legs of such a clip on the body passageway is significantly improved if a reaction surface is provided as a feature of the clip.

Accordingly to the present invention, there is provided a surgical clip for occluding a body passageway, the clip comprising:

a base portion,

at least one resilient limb extending from the base portion and having a free end disposed forward of the base portion, and

a reaction portion mounted to the base portion, the reaction portion defining a generally forwardly directed reaction surface disposed between the base portion and the free end of the limb or limbs,

- the limb or limbs being movable under a resilient restoring force from a first, open, condition, in which a gap is provided between the limb or limbs and the reaction portion for receiving the body passageway into the clip, to a second, closed, condition, in which the limb or limbs cooperate with the reaction portion to grip the body passageway to occlude the same.

## Detailed Description of the Invention

### *Exemplified Features of the Clip*

- Preferably, the limb or limbs of the clip extend generally laterally outwardly from the base portion of the clip. Most preferably, the clip has a pair of such limbs each extending in opposite lateral directions from the base portion of the clip. The base and reaction portions are preferably disposed generally centrally between the pair of limbs.

- The reaction surface is preferably substantially fixed in relation to the movement of the limb or limbs. The reaction surface is preferably elongate. The reaction surface may be straight or curved, and preferably has the form of a ridge or edge. The reaction surface and the limb or limbs are suitably dimensioned and arranged so that in the closed condition of the clip substantially the entire transverse width of the occluded body passageway is in contact with the reaction surface.

- The clip is preferably generally planar, but the respective planes of the parts may be offset against one another. Thus, for example, the plane of the reaction portion may be at a small angle (e.g. up to about 15°) to the plane of the base portion, with a slight twist provided at the region of connection between the two portions. The plane of the or each limb may be at a small angle (e.g. up to about 15°) to that of the base portion. Where the clip has a pair of limbs, it is preferred that one limb lies slightly to one side of the plane of the base portion, and the other limb lies slightly to the opposite side of that plane. The free ends of the limbs thereby overlie each side of the reaction portion – itself preferably lying in a plane which is slightly offset relative to the plane of the base portion - in the closed condition of

the clip. The direction and angular extent of the offsetting of the plane of the reaction portion are preferably such that the free end of a limb approaches close to the reaction surface in the closed condition of the clip, enhancing the grip on an intervening body passageway in comparison with a clip in which the reaction portion would not have been offset from the plane of the base portion. In this way, a particularly efficient and secure occlusive effect can be achieved, with less bending of the limb(s) out of the plane than would have been necessary to achieve the same occluding effect if the plane of the reaction portion were not offset in relation to the base portion.

10

The reaction surface may be shaped in a manner generally complementary to the shape of those parts of the limb or limbs which cooperate with the reaction surface in the second condition of the clip. At least one of the opposed cooperating parts of the reaction surface and the limb or limbs may suitably be provided with surface projections which serve in use to enhance the grip on the body passageway. Such projections may include rounded teeth, pointed teeth, nipping heads, or any combination thereof. Teeth or nipping heads may be turned in the manner of a shark's fin, if desired.

15

At least one of the reaction surface and the limb or limbs may suitably be provided with one or more guide projections which serve during closure of the clip to guide the body passageway to lie in a particular -- preferably central -- region of the clip. The guide projections may conveniently have a rounded shape.

20

The reaction portion of the clip is preferably connected to the base portion via a relatively narrow neck.

25

It is preferred that the or each limb extends from the base portion of the clip behind the reaction portion of the clip and initially turns backwards, i.e. away from the

30

forward facing direction of the reaction surface, and that the or each limb has at least one further turn ("elbow") in its length, after which it extends in the forwards direction to cause the free end of the limb to extend forwardly of the reaction surface. The turns may suitably be smooth curves. Such a configuration has the advantage that the stress applied to open the limbs against the resilient restoring (closing) force of the limbs is spread over a relatively long limb length, so reducing the risk of failure or loss of resilience. Furthermore, by providing for a

35

relatively long limb length, useful leverage or mechanical advantage can be obtained in the closing of the limb towards the reaction surface. The majority of clip closure takes place at the elbow section of the limb. However, when the clip closes around a body passageway there is some straightening of the other turns, as  
5 additional length is transferred from such other sections into the gripping part of the limb, so providing the leverage referred to above.

The base portion of the clip is suitably in the form of an open loop or generally U shaped member having a closed end directed away from the limb or limbs and an  
10 open end from which the limb or limbs and the reaction portion extend. As viewed from above the general plane of the clip, the clip has a left hand side and a right hand side. These sides may preferably be generally symmetrical about a central axis of symmetry. The open ends of the loop preferably lie close to either side of said axis in both the open and the closed conditions of the clip. The  
15 reaction portion of the clip may be connected to the base portion via a single neck region at one of said left and right sides of the loop of the base portion, or alternatively the reaction portion of the clip may be provided in two halves, each of which is connected to one side of the base portion via a neck region. The two halves may be complementarily juxtaposed to provide the reaction surface of the  
20 clip.

The base portion of the clip is preferably provided with a weak region or point at which it may be cut after use in such a way that the clip, in its second, closed, condition, can be removed from the body passageway. The weak region or point  
25 may preferably be provided with a notch or mark to assist the procedure.

The parts of the clip are preferably integral with each other and the clip is preferably formed in one piece from a sheet of a resilient material. The sheet will preferably have a uniform thickness in the range of about 500 to about 1000 $\mu$ m,  
30 depending on the size of clip required. Suitable resilient materials include shape-memory materials whether of the temperature-induced or stress-induced type. Suitable materials are identified in WO-A-00/35355. A useful class of materials is that described generally as superelastic or stress-induced shape-memory materials. Such materials are well known in the art generally. A preferred material is Nitinol  
35 metal (nickel-titanium alloy), more preferably Nitinol having an Active Austenite Finish (Active  $A_f$ ) temperature of around 15°C within normal Nitinol tolerance.



### *Manufacture of the Clip*

The clip may suitably be manufactured by photochemical etching or laser cutting from a sheet of the resilient material. A suitable sheet material will be a flat, annealed, surface pickled, Nitinol sheet of 800 $\mu$ m thickness, available from SMA, Inc. of San Jose, USA (web-site: [www.sma-inc.com](http://www.sma-inc.com)) under Alloy Code S (approx. 55.8 wt% nickel; balance titanium). Such a sheet has an Active  $A_f$  temperature of around 15°C within normal Nitinol tolerance. Laser cutting is preferred. The use of an industrial laser has been found to be advantageous, in that no extraneous metals are added to the surface composition of the clip by this process. The laser cutting technique provides the required degree of accuracy and does not adversely affect the superelasticity of the Nitinol.

The clip is preferably obtained initially as a planar blank with the limb(s) arranged in an intermediate condition, i.e. with the limb(s) neither fully opened, nor too closed to interfere with reaction portion. The intermediate condition should be sufficiently close to the first (open) condition that the first condition of the clip can be obtained by stressing the limb(s) outwardly by less than the maximum recoverable strain of the resilient material used. In the case of Nitinol, its maximum recoverable strain is 6 to 8%, which means in practice that the limb(s) of the blank as cut should lie sufficiently close to its/their orientation in the first condition of the clip that the first condition can be achieved by moving the limb(s) outwardly by an angular deformation of less than about 8°.

Following this, a batch of formed clips will preferably be sandblasted to remove burrs from the cut edges. After this, they undergo a two stage shape setting process (shape set annealing twice).

---

In stage one, the reaction portion of the clip is rotated slightly out of the plane of the blank, sufficient to allow the limb(s) to move easily into the closed condition. The clip is then shape set annealed to permanently set this alteration.

In stage two, the or each limb is turned inwards into the closed condition, e.g. using a jig. In addition, the or each limb is slightly off-set above or below the plane of the blank, to pass in front of, or behind, the reaction portion. The formed

clip is then constrained and heat treated to permanently set the closed shape (shape set annealed).

5 Lastly, the clips are suitably electropolished to round off the edges and the surface passivated by means of a biocompatible oxide or organic coating. Such a coating may suitably comprise titanium dioxide, parylene, or any other conventional biocompatible material.

10 Before opening the clip, cooling needs to be applied to below the Active  $A_f$  temperature of the Nitinol. This technique is used to recover the intermediate condition prior to loading a plurality of clips into the applicator (see below). The clip will then show good superelasticity in response to a stress in a temperature window above the Active  $A_f$  temperature and below body temperature. Under these conditions, the clip will move strongly to its second, closed condition.

15

#### *Use of the Clip*

20 The clip is primarily used to occlude a body passageway during surgery. The term "occlude" refers to an encircling and constricting action, rather than a piercing or cutting action. In some cases, the occlusive effect of the clip should be reversible. The preferred embodiment of the clip of the present invention may be used either for reversible or for irreversible procedures, giving the patient a choice in appropriate cases between reversal and permanence.

25 The clip is preferably applied to the body passageway to be occluded using an applicator apparatus corresponding generally to the apparatus described in WO-A-00/353855. A plurality of clips is held in a train in the apparatus with the limb(s) in an unstressed, intermediate, condition. In this unstressed condition, a substantial superelastic response tending to close the clip will not take place. In

30 response to actuation of the applicator mechanism by the surgeon, one clip is stressed in the apparatus by being moved over a suitably shaped surface so that the limb(s) is/are deflected outwardly by an amount within the maximum recoverable stress of the material of the clip. The clip is then dispensed, limb(s) first, from a port of the apparatus, whereupon the limb(s) immediately close(s) around the body  
35 passageway and occlude(s) the same, preferably without cutting, puncturing or penetrating the body passageway or any adjacent structures. The port of the

apparatus will be such that the clip is not fully released until the clip is well located. Depending on the material from which the clip is manufactured, it may not be necessary for any change in temperature to take place in order to induce the closure of the limb(s) into the second condition of the clip. The stressing immediately prior to dispensing of the clip from the apparatus will in many cases be sufficient to induce the resilient transformation of the clip.

Alternatively, large clips may be applied manually to a body passageway, suitably with the aid of a trocar or other simple stressing device to slightly splay the limbs to activate the superelastic closing force.

Where not otherwise stated herein, the details of the clip of the present invention will correspond generally to the clips defined and described in WO-A-00/35355 where the context permits.

By providing a clip which has a reaction surface as described, the efficacy of the occluding and clamping action of the clip on a body passageway is markedly improved, particularly in the case of small arteries and veins that may otherwise be difficult to close effectively. Furthermore, the clip of the present invention can be readily manufactured in large numbers from a sheet of the resilient material.

The clip will be dimensioned according to the desired use. Typical uses of the clip will include the surgical closure of veins and arteries for haemostasis; ligation; male and female sterilisation; vascular occlusion; cardiac vessel occlusion; the occlusion of body ducts prior to resection; intracranial vessel occlusion for neurosurgery; occlusion of aberrant vessels or aneurysms such as intracranial aneurysm clipping; and occlusion of arterio-venous malformations. In each case, the clip can be dimensioned to be suitable for paediatric, adult or veterinary surgery.

A clip size of about 6mm width will generally be suitable for occluding body passageways having a diameter in the range of about 3 to about 5mm. Corresponding size adjustments can readily be made to cater for different sizes of passageway.

The clips of the present invention may conveniently be supplied in standard sizes, to cater for body passageways within a defined diameter range. It is envisaged that clips may suitably be supplied in sizes suitable for 1-2mm passageways, 2-3mm passageways, 3-5mm passageways, and so on.

5

### **Brief Description of the Drawings**

An embodiment of the present invention will now be described in further detail, purely by way of example and without limitation, with reference to the accompanying drawings.

10

In the drawings:

Figure 1 shows a surgical clip in the first condition applied to a body passageway, looking along the line of the body passageway;

15

Figure 2 shows the surgical clip of Figure 1 omitting the body passageway for clarity, and in dotted lines the resting or intermediate condition of the clip prior to stressing to achieve the first condition;

20

Figure 3 shows the surgical clip and body passageway in the closed condition (occluded body passageway);

Figure 4 shows in perspective the surgical clip and body passageway of Figure 3 from front right; and

25

Figure 5 shows the surgical clip in a fully closed condition achievable without a body passageway.

30

### **Detailed Description of the Drawings**

Referring to the drawings, there is shown a surgical clip 1 for occluding a body passageway 2, e.g. for haemostasis.

The clip 1 comprises a base portion 3 and a pair of resilient limbs 4a, 4b extending laterally outwardly from the base portion. The limbs 4a, 4b are resiliently movable

35

from a first, open, condition (Figure 1; Figure 2, solid lines), in which the limbs are spaced apart to define a gap for receiving the body passageway 2, to a second, closed condition (Figures 3 to 5), in which the limbs 4a, 4b are closed around the body passageway to occlude it. The occlusion of the body passageway is a simple closing (pinching), without puncture or rupture, and can be reversed by removing the clip, as will be described in more detail below.

The base portion 3 of the clip is in the form of an open U-shaped loop having a closed end 5 directed away from the limbs 4a, 4b and open end 6 at which the limbs 4a, 4b are connected.

As shown particularly in Figures 1 and 2, the clip consists of symmetrical left and right parts, the clip having a central axis of symmetry or midline 7. The closed end 5 of the loop is provided with a notch 8 defining a point at which the central body portion 3 of the clip can be cut. Such cutting will release the clip from its closed condition on the body passageway (Figures 3 to 5), to enable removal of the clip from the body passageway.

The clip 1 includes, in separate but complementarily juxtaposed left and right parts 9a, 9b with respect to the central axis of symmetry 7 of the clip, a reaction portion which projects from the base portion and defines, at a location forward of the base portion but behind the free ends of the limbs 4a, 4b an elongate forwardly directed reaction surface 10 arranged cooperate with the limbs 4a, 4b in the second (closed) condition of the clip so that substantially the entire transverse width of the occluded body passageway 2 is in contact with the reaction surface 10 for being gripped between the limbs 4a, 4b and the reaction surface. The reaction surface 10 is in the general form of an edge which serves to pinch the body passageway 2, without severing it.

Each of the left and right parts 9a, 9b of the reaction portion is connected to the respective left or right side of the central body portion 3 of the clip via relatively thin neck 11a, 11b. The reaction surface 10 and the limbs 4a, 4b are provided with rounded guide projections 12 which serve in use to guide the body passageway 2 to lie in a generally central region of clip 1.

- As shown particularly in Figure 4, one limb 4a lies to one side of the edge of the reaction surface 10, i.e. slightly to the left of the vertical plane of the central body portion 3 of the clip as viewed, and the other limb 4b lies to the other side of the edge of the reaction surface 10, i.e. slightly to the right of the plane of the central body portion 3 of the clip as viewed. In addition, the central reaction portion 9a, 9b is rotated (off-set) anticlockwise from the neutral, planar, laser cut condition, to further facilitate movement of each of the limbs 4a, 4b to pass unhindered to its respective side of the reaction surface 10.
- 10 The closure of the limbs 4a, 4b is achieved by a straightening of some curves of the limbs and a tightening of others. The other portions of the clip are configured so that they do not foul the movement of the limbs. As previously explained, the shape of the limbs has been found to provide a useful leverage effect, maximising the occlusive effect within the capabilities of the shape-memory material being used. The location of the reaction surface between the limbs and forward of the central body portion of the clip provides further advantages in that the occlusive effect can be achieved to the desired extent without excessive tightening of any curve of the limbs being required.
- 20 The clip 1 is formed by laser cutting a suitable "blank" shape from a sheet of Nitinol alloy having an Active  $A_f$  temperature of about  $15^\circ\text{C}$ . The thickness of the sheet will be chosen according to the desired dimensions, end use and closing force of the clip. I have found, for example, that a sheet thickness of between about 500 and 1000  $\mu\text{m}$  (e.g. about 800  $\mu\text{m}$ ) is suitable for forming a clip for occluding veins and arteries. The initially cut blank shape is planar and has the shape shown by the dotted lines in Figure 2. The closed condition of the limbs as shown in Figure 5 is then memorised into the clip in the manner described above. The initial orientation of the limbs is selected so that they are capable of being deflected slightly outwards (e.g. by an angle up to about  $8^\circ$ ), within the limit of deformation, to stress the limbs and induce a superelastic or pseudoelastic response, urging the limbs to close when the stress is released. If the clip is not applied to a body passageway, the fully closed condition shown in Figure 5 will result, in which the limbs 4a and 4b lie across the off-set central reactive portion 9a and 9b. If, on the other hand, the clip is applied to a body passageway as described above, it will close to the condition shown in Figures 3 and 4 when the stress is released.

After memorising of the shape, the clips are electropolished to round off the edges and a passive, closed layer of titanium dioxide is created (surface passivation), which is more biocompatible than the metal. The electropolishing process reduces the clip thickness to about 730-750 $\mu$ m. The active  $A_f$  of the finished product is around 15°C, which means that the clips are superelastic, but also exhibit shape memory function (Austenite closed shape preference) at temperatures above 15°C. Chemical analysis confirms that the final composition of the clip contains 50.91 at% nickel and that the nickel content at the surface, following surface passivation, is <5 at %. The deposited surface layer of titanium dioxide is approximately 50-80 nm thick, which has been found to produce good biocompatibility.

The foregoing broadly describes the invention without limitation to particular embodiments thereof. Variations and modifications as will be readily apparent to those of ordinary skill in this art are intended to be included within the scope of this application and subsequent patent(s).

20

25

---

CLAIMS

1. A surgical clip for occluding a body passageway, the clip comprising:  
a base portion,  
5 at least one resilient limb extending from the base portion and having a free end disposed forward of the base portion, and  
a reaction portion mounted to the base portion, the reaction portion defining a generally forwardly directed reaction surface disposed between the base portion and the free end of the limb or limbs,  
10 the limb or limbs being movable under a resilient restoring force from a first, open, condition, in which a gap is provided between the limb or limbs and the reaction portion for receiving the body passageway into the clip, to a second, closed, condition, in which the limb or limbs cooperate with the reaction portion to grip the body passageway to occlude the same.  
15
  2. A surgical clip according to claim 1, wherein the clip has a pair of such limbs each extending in generally opposite lateral directions from the base portion of the clip.
  - 20 3. A surgical clip according to claim 2, wherein the base and reaction portions are disposed generally centrally between the pair of limbs.
  4. A surgical clip according to any one of the preceding claims, wherein the reaction surface is substantially fixed in relation to the movement of the limb or  
25 limbs.
  5. A surgical clip according to any one of the preceding claims, wherein the reaction surface is elongate.
- 
- 30 6. A surgical clip according to any one of the preceding claims, wherein the reaction surface and the limb or limbs are suitably dimensioned and arranged so that in the closed condition of the clip substantially the entire transverse width of the occluded body passageway is in contact with the reaction surface.
  - 35 7. A surgical clip according to any one of the preceding claims, wherein the respective planes of the parts of the clip are offset against one another.



8. A surgical clip according to any one of the preceding claims, wherein the plane of the base portion is at a small angle to the plane of the reaction portion.

5 9. A surgical clip according to any one of the preceding claims, wherein the plane of the or each limb is at a small angle to that of the other parts.

10 10. A surgical clip according to any one of the preceding claims, wherein the clip has a pair of limbs, one limb lies slightly to one side of the planes of the base and reaction portions, and the other limb lies slightly to the opposite side of those planes, whereby the free ends of the limbs overlies opposite sides of the reaction portion in the closed condition of the clip.

15 11. A surgical clip according to any one of the preceding claims, wherein the reaction surface is shaped in a manner generally complementary to the shape of those parts of the or each limb which cooperate with the reaction surface in the closed condition of the clip.

20 12. A surgical clip according to any one of the preceding claims, wherein at least one of the opposed cooperating parts of the reaction surface and the or each limb is provided with surface projections which serve in use to enhance grip of the clip on the body passageway.

25 13. A surgical clip according to claim 12, wherein the surface projections are rounded teeth, pointed teeth, nipping heads, or any combination thereof.

30 14. A surgical clip according to any one of the preceding claims, wherein the or each limb is connected to the base portion of the clip via a curved portion of the limb defining a connection point to the base portion behind the reaction portion of the clip.

15. A surgical clip according to claim 14, wherein a further curve is provided in the limb in the opposite direction to the said curved portion, whereby free end of the limb is disposed forward of the base portion of the clip.

35 16. A surgical clip according to claim 14 or claim 15, wherein an elongate portion is provided in the or each limb between the curves, whereby during closure

a leverage effect is produced on the part of the limb which is in contact with the body passageway.

5 17. A surgical clip according to any one of the preceding claims, wherein the base portion of the clip is in the form of an open loop or generally U shaped member having a closed end directed away from the limbs and an open end at which the limbs and the reaction portion are connected to the base portion.

10 18. A surgical clip according to claim 17, wherein the reaction portion of the clip is provided in two halves, each of which is connected to one side of the open end of the base portion via a neck region and which are complementarily juxtaposed to define the reaction surface of the clip.

15 19. A surgical clip according to any one of the preceding claims, wherein the base portion of the clip is provided with a weak region or point at which the base portion may be cut to remove the clip from the body passageway.

20 20. A surgical clip according to any one of the preceding claims, wherein the clip is integrally formed of a superelastic or pseudoelastic shape-memory material.

21. A surgical clip according to any one of the preceding claims, wherein the clip is integrally formed of sheet nitinol metal (nickel-titanium alloy).

25 22. A surgical clip substantially as herein described with reference to the accompanying drawings.

---

ABSTRACTSURGICAL CLIP

- 5 A surgical clip for occluding a vein, artery or other body passageway 2 comprises  
a base portion 3, a pair of resilient limbs 4a, 4b configured to extend generally  
laterally outwardly from the base portion and each having a free end disposed  
forward of the base portion, and a reaction portion 9a/b mounted to the base  
portion 3, the reaction portion defining a generally forwardly directed reaction  
10 surface 10 disposed between the base portion 3 and the free ends of the limbs 4a,  
4b, the being movable under a resilient restoring force from a first, open,  
condition, in which a gap is provided between the limbs and the reaction portion  
for receiving the body passageway into the clip, to a second, closed, condition, in  
which the limbs cooperate with the reaction portion to grip the body passageway to  
15 occlude the same.

Figures 1, 3

---

Figure 1.




Figure 2.




Figure 3.




Figure 4.





Figure 5.





This Page is inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLORED OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REPERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images  
problems checked, please do not report the  
problems to the IFW Image Problem Mailbox**